

DRIVER: SCOTT HARP TRUCK NAME: MAGNUM BODY: JCONCEPTS 2022 RAPTOR
EVENT: OFF TRACK RC OFFTOBERFAST DATE: QUAL: TQ FINISH: 1ST
TRACK: JB SCALE GRAPHICS SURFACE TYPE: DIRT Size: Small / Med / Large / Very Large
TRACTION: Low / Med / High / Very High CONDITION: Dry / Damp / Wet / Dusty / Hard Pack / Bumpy
TEMPERATURE: WEATHER: Smooth / Loamy / Other:

Other Towers:
Digger LMT / Mega LMT / TLR LMT / LMT 2.0 / Other:

REAR

FRONT

DUO TOWER: Y / N
Rear Shock Mount Location

Limit Strap Location
Length: NA mm
(fill in both for inbetween)

Sway Bar
Type: TREAL
Thickness: mm
Length: mm

Rear Axle Weights: Y / N
Type:
Added weight: 1.5 OZ

Eye to Eye Upper
Link Length: 140 mm

Rear Diff Oil: 60K

Rear Wheels:

Tire: RENEGADE BLUE

Insert: JCONCEPTS SLAM
TECH

Tire Mods:

Wheels: TRIBUTE

Track Width:

Rear Toe: 0° / 3° / 3 °

Eye to Eye
Link Length: mm

STL Shock Location:

Wheelbase: 15"

Ride Height:

Running Weight:

Electronics

ESC: TEKIN RX4

Battery: PROTEK 2S

Motor: TEKIN PRO4 HD 4300KV

Servo: REEFS RAW 500

Accessories:

Notes:

Model: LOSI TLR
Cap Bladder: Y/N
Pre Load: 7 mm
Shock Length: 105 mm
Oil: 40WT
Piston: 1.4
Spring: LOSI ORANGE
Bump Stop: NA mm
Type:

Model: LOSI TLR
Cap Bladder: Y/N
Pre Load: 7 mm
Shock Length: 105 mm
Oil: 40WT
Piston: 1.4
Spring: LOSI ORANGE
Bump Stop: NA mm
Type:

ESC Location

Motor Location: RR / RF / LR / LF

Center Diff Oil: 300K
Ring Gear Orientation: F / R

Pinion: 15

Skid Plate: Y / N
Type:

Battery Brass Weight: Y / N
Grams Total: NA

Chassis Skid Weights: Y / N
Grams Total:

DUO TOWER: Y / N
Front Shock Mount Location

Limit Strap Location
Length: NA mm
(fill in both for inbetween)

Sway Bar
Type: TREAL
Thickness: mm
Length: mm

Servo Saver: Y / N
Make & Model:
REEFS

Steering Limit: Y / N
Degrees:

STL TOWER: Y / N
Shock Location
(fill in both for inbetween)

Front Upper
Link Location

Eye to Eye Upper
Link Length: 140 mm

Front Diff Oil: 60K

Front Wheels:

Tire: RENEGADE BLUE

Insert: JCONCEPTS SLAM
TECH

Tire Mods:

Wheels: TRIBUTE

Track Width:

Front Toe: 1 °

Caster: 10 °

Eye to Eye
Link Length: mm

STL Shock Location: